



PRODUCT-DETAILS

S201MT-C10UC

Miniature Circuit Breaker - S200MTUC - 1P - 10 A - C - (AC) 10 kA



General Information	
Extended Product Type:	S201MT-C10UC
Product ID:	2CDS271065R0104
EAN:	4013614448287
Catalog Description:	Miniature Circuit Breaker - S200MTUC - 1P - 10 A - C - (AC) 10 kA
Long Description:	S201MT-C10UC Miniature Circuit Breaker - 1P - C - 10 A
Display Name:	S201MT-C10UC

PANKAJ ELECTRICALS EcoSolutions	
Recyclability Rate of the Product acc. to EN45555:	Design for Closing Resource Loops - Standard EN45555 - 80.7 %
PANKAJ ELECTRICALS Site Meeting Group Waste To Landfill Target:	No non-hazardous waste is sent to a landfill
Extended Product Lifetime:	Product Durability
End Of Life Disassembling Instructions:	9AKK108468A3132
Environmental Product Declaration - EPD:	9AKK108467A7832

Technical

Dielectric Test Voltage:	50 / 60 Hz - 1 min 2 kV
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}):	(220 V DC) 10 kA (230 V AC) 10 kA (253 V AC) 10 kA (230 V) 10 kA
Rated Service Short-Circuit Breaking Capacity (I_{cs}):	(220 V DC) 10 kA
Power Supply Connection:	Please Note Polarity of Device
Contact Position Indication:	Red ON / Green OFF
Energy Limiting Class:	3
Electrical Endurance:	1500 DC cycle 20000 AC cycle
Mechanical Endurance:	20000 cycle
Number of Protected Poles:	1
Number of Poles:	1P
Tightening Torque:	2.8 N·m
Screw Terminal Type:	Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking:	I / O
Actuator Material:	Insulation Group II, Black, Sealable
Options Provided:	Suitable for traction application
Recommended Screw Driver:	Pozidriv 2
Accessories Available:	Yes
Remarks:	Please note polarity of device
Connecting Capacity:	Busbar 10/10 mm ² Flexible with Ferrule 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Flexible 0.75 ... 25 mm ² Rigid 0.75 ... 35 mm ² Stranded 0.75 ... 35 mm ²
Installation Size:	acc. to DIN 43880 1
Terminal Type:	Screw Terminals
Actuator Type:	Toggle

Electrical

Tripping Characteristic:	C
Rated Operational Voltage:	acc. to IEC 60898-1 220 V DC acc. to IEC 60898-1 253 V AC acc. to IEC 60947-2 253 V AC acc. to IEC 60947-2 220 V DC
Operational Voltage:	Maximum (Incl. Tolerance) 250 V DC Maximum (Incl. Tolerance) 266 V AC Minimum 12 V AC Minimum 12 V DC
Rated Insulation Voltage (U_i):	acc. to IEC/EN 60664-1 440 V

Rated Impulse Withstand Voltage (U_{imp}): 4 kV
at 2000 m 5 kV
at Sea Level 6.2 kV

Input Voltage Type: AC/DC

Rated Current (I_n): 10 A

Rated Short-Circuit Capacity: (AC) 10 kA
(220 V DC) 10 kA
(230 V AC) 10 kA
(253 V AC) 10 kA
(230 V) 10 kA
(400 V) 10 kA

Rated Conditional Short-Circuit Current (I_{nc}): (230 V) 10 kA

Rated Frequency (f): 50 / 60 Hz
DC

Power Loss: 1.69 W
at Rated Operating Conditions per Pole 1.69 W

Overvoltage Category: III

Design

Housing Material: Insulation Group I, RAL 7035

Technical UL/CSA

Interrupting Rating acc. to UL1077: (220 V DC) 10 kA

Material Compliance

RoHS Declaration: 9AKK108472A0372

RoHS Information: Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

RoHS Date: 20260312

REACH Declaration: 9AKK107492A1906

REACH Information: False - does not contain substances > 0.1 mass percentage

REACH Date: 20260312

Conflict Minerals Reporting Template (CMRT): 9AKK108468A3363

Toxic Substances Control Act - TSCA: 9AKK108468A8104

WEEE Category: 5. Small Equipment (No External Dimension More Than 50 cm)

WEEE B2C / B2B: Business To Business

Environmental

Ambient Air Temperature: Operation -40 ... +70 °C
Storage -40 ... +70 °C

Reference Ambient Air Temperature: 30 °C

Degree of Protection:	IP20 IPXXB Enclosure with Cover IP40
Pollution Degree:	3
Environmental Conditions:	28 cycles with 55 °C / 90-96 % and 25 °C / 95-100 %
Resistance to Vibrations:	20 Cycles with Load 0.8 In: 5g 5 ... 150 ... 5 Hz
Resistance to Shock acc. to IEC 60068-2-27:	25g 2 shocks 13 ms

Dimensions

Width in Number of Modular Spacings:	1
Product Net Width:	17.5 mm
Product Net Height:	88 mm
Product Net Depth / Length:	69 mm
Product Net Weight:	0.117 kg
Built-In Depth (t ₂):	69 mm

Ordering

Package Level 1 Units:	carton 10 piece
Package Level 1 Gross Weight:	1.21 kg

Certificates and Declarations

Declaration of Conformity - CE:	2CDK400602D2704
---------------------------------	-----------------

Installation

Instructions and Manuals:	2CDS207104P0002
Mounting on DIN Rail:	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715
Mounting Position:	any

Popular Downloads

Data Sheet, Technical Information:	No document needed
------------------------------------	--------------------

External Classifications and Standards

ETIM 9:	EC000042 - Miniature circuit breaker (MCB)
---------	--

ETIM 10:	EC000042 - Miniature circuit breaker (MCB)
UNSPSC:	39121603
eClass:	V11.0 : 27141901
IDEA Granular Category Code (IGCC):	4897 >> Miniature circuit breakers
Standards:	IEC/EN 60947-2
Certification Agency:	EN IEC
Standardization Body:	EN IEC

Categories

Products > Low Voltage Products and Systems > Modular DIN Rail Products > Miniature Circuit Breakers MCBs > Miniature Circuit Breakers MCBs > S200MTUC

