



PRODUCT-DETAILS

K675TBC
APPARATUS BSHG W/COLLAR



General Information	
Extended Product Type:	K675TBC
Product ID:	7TAA123780R0044
EAN:	5415022341843
Catalog Description:	APPARATUS BSHG W/COLLAR
Long Description:	15/25kV, 900 Amp, Deadbreak Bushing for In-Air Applications (Pad-Mounted or Vault-Type or Submersible Transformers or Switchgear). One Factory installed 5/8-11 UNC-2A Stud included, other Stud must be Purchased Separately. Overall Length 13.75 inch, Diameter 4.50 inch. Molded Epoxy with Stainless Steel Flange. Boot and Collar.
Display Name:	K675TBC

Ordering	
EAN:	5415022341843
UPC:	783786629725
Country of Origin:	United States
Selling Unit of Measure:	each

Container Information

Package Level 1 Units:	1 EA
Package Level 1 Width:	0.025 mm 0.001 in
Package Level 1 Height:	0.025 mm 0.001 in
Package Level 1 Depth / Length:	0.025 mm 0.001 in

Additional Information

Application:	In-Air Applications
Brand / Label:	ELASTIMOLD
Effective Date:	19980108
Material:	Molded Epoxy Body and Stainless Steel Flange
Product Name:	Terminals, electrical splices and electrical couplings
Product Type:	Deadbreak Bushing - 900 Amps
Size:	Overall Length 13.75 inch, Diameter 4.50 inch.
Special Functions:	Conductive Shield made of Molded Conductive EPDM makes Positive Ground Contact with EPDM Flange of Bushing Insert. Stainless Steel Flange Resists Corrosion and can be Externally Clamped or Welded to Apparatus.
Standards:	ANSI/IEEE Standard 386
Temperature Range:	-40 to +65 °C

External Classifications and Standards

UNSPSC:	26121630
IDEA Granular Category Code (IGCC):	1779 >> Cable accessories

Material Compliance

RoHS Information:	No declaration needed
WEEE Category:	Product Not in WEEE Scope

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Accessories and Apparatus > Cable Accessories > Elastimold Joints, Terminations, Misc.

