



PRODUCT-DETAILS

HNC12/100M

12MM SOLID PA12 CONDUIT 100M - BL



General Information	
Extended Product Type:	HNC12/100M
Product ID:	7TCA298000R0163
EAN:	5020963047282
Catalog Description:	12MM SOLID PA12 CONDUIT 100M - BL
Long Description:	Low Temperature, Extra Flexible Conduit, NC Size 12/NW Size 10, Outside Diameter 13.0mm, Inside Diameter 9.9mm, Static Bend Radius 25mm, Very High UV Resistance and Fatigue Life, IP40 Rating, Polyamide 12, Reel Length 100 Meters, Black
Display Name:	HNC12/100M

Additional Information	
Product Main Type:	HARNESSFLEX FLEXIBLE CABLE PROTECTION
Application:	Used in Applications Requiring Repeated Flexing Coupled with Low Temperature Impact Resistance, Such as Robotics or Rapid Continuous Motion, Demanding High Fatigue Life and Extra Flexibility Even in Low Temperature Environments

Ordering

EAN: 5020963047282

UPC: 786210244822

Dimensions

Product Net Weight: 5.733 lb
2.6 kg

Outside Diameter: 13.0 mm

Technical

Number of Batteries: 0

Color: Black

Material: Polyamide/Nylon 12

Environmental

WEEE Category: Product Not in WEEE Scope

RoHS Information: Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units: 1 piece

Package Level 1 EAN: 5020963047282

Package Level 1 Height: 6.3 in
160 mm

Package Level 1 Depth / Length: 18.11 in
460 mm

Package Level 1 Width: 18.11 in
460 mm

Certificates and Declarations

Declaration of Conformity - CE: 9AKK107492A9616

RoHS Declaration: 9AKK107992A8994

REACH Declaration: 9AKK107992A8994

External Classifications and Standards

ETIM 8: EC001175 - Corrugated plastic hose

ETIM 9: EC001175 - Corrugated plastic hose

UNSPSC: 39131706

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems > Harnessflex Flexible Cable Protection

