



PRODUCT-DETAILS

HTC16/50M

16MM SOLID PE CONDUIT 50M - BR

General Information	
Extended Product Type:	HTC16/50M
Product ID:	7TCA298010R1129
EAN:	5020963805370
Catalog Description:	16MM SOLID PE CONDUIT 50M - BR
Long Description:	Medium Weight, High Flexibility Conduit, Conduit Size NC16/NW13, Very High UV Protection, Operating Temperature -50 (Static Use)/-45 (Dynamic Use) to 150 Degrees Celsius, IP40 Rating with TempGuard and Standard Hinged Fittings, IP67 Rating with Sealed Fittings, 50 Meter Reel Length, Modified Co-Polyester, Black
Display Name:	HTC16/50M

Additional Information	
Product Main Type:	HARNESSFLEX FLEXIBLE CABLE PROTECTION
Application:	Suited to Static and Dynamic Applications Where Elevated Temperatures are Present. HTC is Resistant to All Under Bonnet Greases, Fuels and Oils

Ordering	
EAN:	5020963805370
UPC:	786210290393

Dimensions	
Product Net Weight:	5.122215 lb 2.323 kg

Technical	
Number of Batteries:	0
Color:	Black

Material: Modified Co-Polyester

Environmental

WEEE Category: Product Not in WEEE Scope

RoHS Information: Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units: 1 piece

Package Level 1 EAN: 5020963805370

Package Level 1 Height: 5.91 in
150 mm

Package Level 1 Depth / Length: 16.54 in
420 mm

Package Level 1 Width: 16.54 in
420 mm

Certificates and Declarations

Declaration of Conformity - CE: 9AKK107492A9616

RoHS Declaration: 9AKK107992A8994

REACH Declaration: 9AKK107992A8994

External Classifications and Standards

ETIM 8: EC001175 - Corrugated plastic hose

ETIM 9: EC001175 - Corrugated plastic hose

UNSPSC: 39131706

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems > Harnessflex Flexible Cable Protection